

### **Physical-Technical Testing Institute** Ostrava - Radvanice



## **EU - Type Examination Certificate**

(2)

**Equipment or Protective Systems Intended for Use** in Potentially Explosive Atmospheres (Directive 2014/34/EU)

(3) EU - Type Examination Certificate number:

### **FTZÚ 16 ATEX 0138X**

(4) Product:

Capacity Level Meter type DLM-35Xi (XiT, XiM, XiMT)

(5) Manufacturer:

Dinel, s.r.o.

(6) Address:

U Tescomy 249, 760 01 Zlín, Czech Republic

- (7) This product and any acceptable variation thereto is specified in the schedule to this certificate and the documents therein referred to.
- (8) The Physical-Technical Testing Institute, Notified Body number 1026, in accordance with Articles 17 of Directive 2014/34/EU of the European Parliament and of the Council, dated 26.02.2014, certifies that this product has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of products intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The examination and test results are recorded in confidential Report number:

16/0138 dated 01.03.2017

(9) Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

#### EN 60079-0:2012, EN 60079-11:2012, EN 50303:2000

- (10) If the sign "X" is placed after the certificate number, it indicates that the product is subject to Specific Conditions of Use specified in the schedule to this certificate.
- (11) This certificate relates only to the design and construction of the specified product. Further requirements of the Directive apply to the manufacturing process and supply of this product. These are not covered by this certificate.
- (12) The marking of the product shall include the following:

II 1G Ex ia IIB T4 Ga

II 1D Ex ia IIIC T120°C Da

version Xi

II 1/2G Ex ia IIB T4 Ga/Gb

II 1/2D Ex ia IIIC T120°C Da/Db version XiT

IM1 Exial Ma

version XiM, XiMT

This certificate is valid till:

01.03.2022

Responsible person:

Dipl. Ing. Lukáš Martinák Head of Certification Body

Date of issue: 01.03.201

Page: 1/3

This certificate is granted subject to the general conditions of the FTZÚ, s.p. This certificate may only be reproduced in its entirety and without any change, schedule included.



# Physical-Technical Testing Institute Ostrava - Radvanice

(13)

#### Schedule

## (14) EU - Type Examination Certificate No. FTZÚ 16 ATEX 0138X

#### (15) Description of Product:

The product Capacity Level Meter type DLM-35Xi (XiM, XiT, XiMT) is designed to continual measuring of level of liquids, loose substances in storage tanks, containers, etc. It is contains of steel enclosure with electronic and sensing electrode. The level of surface is convert to current signal 4-20mA. The level transducers are producing in some modification of sensing electrodes, bars or cables, with insulated electrode or non-insulated electrode, with connection by solid cable with plastic or metallic glands or with connection by connector. All versions are produced in modification for high processing temperature marked DLM-35XiT (XiMT). There are several types with different procedural connection (metric pipe thread, pressure thread NPT).

Intrinsically safe parameters:

Ui = 30 VDC, Ii = 132 mA, Pi=0,99 W, Li = 10  $\mu$ H, Ci = 35 nF

Ambient temperature: -40°C ≤ Ta ≤ +75°C

(16) Report Number .:

16/0138

#### (17) Specific Conditions of Use:

- Connected intrinsically safe apparatus must be galvanically separated or in the case of using the apparatus without galvanic separation (Zenner barrier) it is necessary to carry out the equalization of potentials between transducer and the place of barriers.
- The version DLM-35Xi can be placed into Zone 0 or Zone 20. For the implementation DLM-35XiT the
  only sensing electrode can be placed into Zone 0 or Zone 20, the head with electronics can be placed
  only into Zone 1 or Zone 21. The maximal temperature sensing electrodes is given by temperature of
  measured material.
- 3. For the implementation DLM-35XiMT must be observed that the temperature of any surface, where coal dust can form a layer, does not exceed 150°C.

#### (18) Essential Health and Safety Requirements:

Compliance with the Essential Health and Safety Requirements is covered by standards mentioned in clause (9) of this certificate.

Responsible person:

Dipl. Ing. Lukáš Martinák Head of Certification Body Date of issue: 01.03.2017

Page: 2/3

This certificate is granted subject to the general conditions of the FTZÚ, s.p.

This certificate may only be reproduced in its entirety and without any change, schedule included.



# Physical-Technical Testing Institute Ostrava - Radvanice

(13)

#### Schedule

## (14) EU - Type Examination Certificate No. FTZÚ 16 ATEX 0138X

#### (19) Drawings and Documents:

Number:	Sheets:	Date:	Description:
DLx-35	11	05.2015	Production Documentation
DLx-35	18	05.2016	Technical Conditions
DLM-35	24	05.2016	User Manual
DLx-35-SV-01	1	04.03.2016	List of Drawings
DLX-35-230	1	22.07.16	Set DL3520, 21, 22
DLX-35-250	1	22.07.16	Set DL3523, 25
DLX-35-300	1	22.07.16	Set DL3530
DLX-35-330	1	22.07.16	Set DL3531
DLX-35-400	1	22.07.16	Set DL3540
DLX-35-450	1	22.07.16	Set DL3541
DLX-35-480	1	22.07.16	Set DL3543, 45
DLX-35-500	1	22.07.16	Set DL3550
DLX-35-900	1	22.07.16	Set DL35_T

Responsible person:

Dipl. Ing. Lukáš Martinák Head of Certification Body



Date of issue: 01.03.2017

Page: 3/3

This certificate is granted subject to the general conditions of the FTZÚ, s.p. This certificate may only be reproduced in its entirety and without any change, schedule included.